



Bucket Elevators



- Galvanized construction ensures Sukup Bucket Elevators will last and look good for years to come.
- Fully adjustable throat plate.
- UHMW seals on all shafts.
- Durable SOFR (static conductive, oil resistant, fire retardant) rubber belting
- 8" x 8" access door on boot allows for easy pulley hub adjustment.



Sukup Manufacturing Co. ■ www.sukup.com

Box 677 ■ 1555 255th St. ■ Sheffield, IA 50475-0677 ■ Phone: 641-892-4222
Fax: 641-892-4629 ■ Email: info@sukup.com

Six Distribution
Centers
To Serve You
Better

Arcola, IL 61910
980 E. State Rd.
Phone: 217-268-3026
Fax: 217-268-3522

Aurora, NE 68818
1705 Hwy. 34 E.
Phone: 402-694-5922
Fax: 402-694-5921

Defiance, OH 43512
7724 Rte. 66 N.
Phone: 419-784-9871
Fax: 419-784-9872

Jonesboro, AR 72403
5917 E. Johnson Ave.
Phone: 870-932-7547
Fax: 870-933-8946

Cameron, MO 64429
7426 NE 352nd St.
Phone: 816-649-2226
Fax: 816-649-2225

Watertown, SD 57201
2701 Piper Ave.
Phone: 605-882-6697
Fax: 605-884-0467



Bucket Elevator Specifications

	24" Pulley	30" Pulley	36" Pulley	42" Pulley	48" Pulley
Capacity BPH	1500-3500	4000-7000	6000-10,000	8000-15,000	12,000-50,000
Trunk Size	13" x 10"	18" x 12"	18" x 12"	22" x 14"	Varies
Head Bearing	Ball	Ball	Roller	Roller	Roller
Std. Belt	220# rubber	330# rubber	330# rubber	450# rubber	Varies

Sukup Manufacturing Co provides the information contained within this brochure to assist you in choosing the optimal equipment for your situation. Many factors, such as grain variety, maturity levels, grain cleanliness, weather conditions and operation/management, can affect the performance of your equipment and results may vary. This information is calculated and is not a guarantee of product specifications or performance. Based on these factors, Sukup specifications should only be used as estimates, and not as a warranty, express or implied, of how a particular Sukup unit will perform under your operating conditions. Because we are continually improving Sukup products, changes may occur that may not be reflected in the specifications.

Sukup Bucket Elevator Heads

- Low impact head design for gentle material handling.
- Split style hood allows for easy interior accessibility.
- Adjustable slide motor mounts.
- 1/4" head and hood lining standard on 36" and larger models (optional on others).
- Crown faced head pulley with slide lagging.
- Large service doors.
- Pressure relief doors standard on 36" and larger models (optional on others).
- Bearing jacking bolts for easy belt alignment.
- Fully adjustable throat plate.



Sukup Bucket Elevator Trunking

- Heavy gauge Huck bolted or seam welded units based on application.
- Alignment ties at the top and bottom of each 10' joint.
- Pressure relief vents optional.
- 5' inspection section to monitor belt & buckets.



Sukup Bucket Elevator Boots

- Externally mounted pillow block bearings.
- Plated ACME threaded take-up screws.
- Heavy-duty angle iron frame for added strength.
- Crown faced boot pulley (optional wing pulley)
- Standard inlet (optional flared inlet)
- Optional shovel pocket.
- Easy access clean-out doors on each end.
- Optional gravity take-up unit for high capacity models.